



Features:

- AC to AC Control Transformer
- AS.NSZ 61558-1
- Max operation temperature : 130°C
*Equals ambient + Case temperature
- Class B : Electrical Insulation
- IP20
- 1 year warranty

Model		PRIMARY (INPUT)	SECONDARY (OUTPUT)	RATED POWER	DIMS A x B x C	DIMENSION D	DIMENSION E	KG
TX40	TX40-240-12	240VAC	12VAC	40VA	78 x 72 x 90	56	46	1.4
	TX40-240-24	240VAC	24VAC	40VA				
	TX40-240-110	240VAC	110VAC	40VA				
	TX40-415-24	415VAC	24VAC	40VA				
	TX40-415-110	415VAC	110VAC	40VA				
	TX40-415-240	415VAC	240VAC	40VA				
TX63	TX63-240-24	240VAC	24VAC	63VA	78 x 72 x 95	56	46	1.5
TX100	TX100-240-12	240VAC	12VAC	100VA	84 x 75 x 96	64	62	2.3
	TX100-240-24	240VAC	24VAC	100VA				
	TX100-240-110	240VAC	110VAC	100VA				
	TX100-415-24	415VAC	24VAC	100VA				
	TX100-415-110	415VAC	110VAC	100VA				
	TX100-415-240	415VAC	240VAC	100VA				
TX160	TX160-240-24	240VAC	24VAC	160VA	96 x 92 x 105	84	73.5	2
TX250	TX250-240-12	240VAC	12VAC	250VA	96 x 100 x 104	84	85	3.4
	TX250-240-24	240VAC	24VAC	250VA				
	TX250-240-110	240VAC	110VAC	250VA				
	TX250-415-24	415VAC	24VAC	250VA				
	TX250-415-110	415VAC	110VAC	250VA				
	TX250-415-240	415VAC	240VAC	250VA				
TX400	TX400-240-12	240VAC	12VAC	400VA	120 x 100 x 122	90	85	5.6
	TX400-240-24	240VAC	24VAC	400VA				
	TX400-240-110	240VAC	110VAC	400VA				
	TX400-415-24	415VAC	24VAC	400VA				
	TX400-415-110	415VAC	110VAC	400VA				
	TX400-415-240	415VAC	240VAC	400VA				
TX630	TX630-240-24	240VAC	24VAC	630VA	150 x 110 x 140	122	90	8.4
TX800	TX800-240-24	240VAC	24VAC	800VA	150 x 128 x 142	122	105	9.5
TX1000	TX100-415-240	415VAC	240VAC	100VA0	150 x 128 x 142	126	152	12.5
TX2500	TX2500-240-110	240VAC	110VAC	2500VA	194 x 250 x 170	170	200	28.7
	TX2500-415-24	415VAC	24VAC	2500VA				
	TX2500-415-110	415VAC	110VAC	2500VA				
	TX2500-415-240	415VAC	240VAC	2500VA				

Note: DIN Rail Mounting is not available for transformers above 100VA
Other primary and secondary options available upon request

