

**Single Phase Control Transformer**



**Features:**

- AC to AC Control Transformer
- AS.NSZ 61558-1
- Max operation temperature : 130°C  
\*Equals ambient + Case temperature
- Class B : Electrical Insulation
- IP20
- 1 year warranty

**240VAC Series**

Model	PRIMARY (INPUT)	SECONDARY (OUTPUT)	RATED POWER	
TX40	TX40-240-12	240VAC	12VAC	40VA
	TX40-240-24	240VAC	24VAC	40VA
	TX40-240-110	240VAC	110VAC	40VA
TX63	TX63-240-24	240VAC	24VAC	63VA
TX100	TX100-240-12	240VAC	12VAC	100VA
	TX100-240-24	240VAC	24VAC	100VA
	TX100-240-110	240VAC	110VAC	100VA
	TX100-240-240	240VAC	240VAC	100VA
TX160	TX160-240-24	240VAC	24VAC	160VA
	TX160-240-110	240VAC	110VAC	160VA
TX250	TX250-240-12	240VAC	12VAC	250VA
	TX250-240-24	240VAC	24VAC	250VA
	TX250-240-110	240VAC	110VAC	250VA
TX400	TX400-240-12	240VAC	12VAC	400VA
	TX400-240-24	240VAC	24VAC	400VA
	TX400-240-110	240VAC	110VAC	400VA
TX500	TX500-240-110	240VAC	110VAC	500VA
	TX500-240-240	240VAC	240VAC	500VA
TX630	TX630-240-24	240VAC	24VAC	630VA
TX800	TX800-240-24	240VAC	24VAC	800VA
	TX800-240-110	240VAC	110VAC	800VA
TX1000	TX1000-240-110	240VAC	110VAC	1000VA
	TX1000-240-240	240VAC	240VAC	1000VA
TX2500	TX2500-240-110	240VAC	110VAC	2500VA

**415VAC Series**

Model	PRIMARY (INPUT)	SECONDARY (OUTPUT)	RATED POWER	
TX40	TX40-415-24	415VAC	24VAC	40VA
	TX40-415-110	415VAC	110VAC	40VA
	TX40-415-240	415VAC	240VAC	40VA
TX100	TX100-415-24	415VAC	24VAC	100VA
	TX100-415-110	415VAC	110VAC	100VA
	TX100-415-240	415VAC	240VAC	100VA
TX250	TX250-415-24	415VAC	24VAC	250VA
	TX250-415-110	415VAC	110VAC	250VA
TX400	TX400-415-24	415VAC	24VAC	400VA
	TX400-415-110	415VAC	110VAC	400VA
TX800	TX800-415-24	415VAC	24VAC	800VA
	TX800-415-110	415VAC	110VAC	800VA
	TX800-415-240	415VAC	240VAC	800VA
TX1000	TX1000-415-110	415VAC	110VAC	1000VA
	TX1000-415-240	415VAC	240VAC	1000VA
TX2500	TX2500-415-24	415VAC	24VAC	2500VA
	TX2500-415-110	415VAC	110VAC	2500VA
	TX2500-415-240	415VAC	240VAC	2500VA

**Note:** DIN Rail Mounting is not available for transformers above 100VA  
Other primary and secondary options available upon request

**Dimensions**

Model	DIMS A x B x C	DIMENSION D	DIMENSION E	KG
TX40	78 x 72 x 90	56	46	1.4
TX63	98 x 72 x 90	56	46	1.4
TX100	84 x 75 x 96	64	62	2.3
TX160	96 x 92 x 105	84	73.5	2.3
TX250	96 x 100 x 104	84	85	3.4
TX400	120 x 100 x 122	90	85	5.6
TX500	120 x 110 x 122	120	110	6.3
TX630	150 x 110 x 140	122	90	8.4
TX800	150 x 128 x 142	122	105	9.5
TX1000	150 x 205 x 130	130	167	12.5
TX2500	194 x 250 x 170	170	200	28.7

