SUNRICHER

Art-Net to DMX Bidirectional converter

SR-2100ArtNet-DMX



Features:

- Bidirectional Art-Net and DMX signal conversion
- Supports up to 4 DMX universes
- LCD display for configuration
- SD card programme playback
- IP20 design for indoor installation
- 2-year warranty

Model		SR-2100ArtNet-DMX
Connectivity	DMX	4 x RJ45
	Network	2 x RJ45
DMX Features	Supported protocols	DMX512, DMX512-A
	DMX Port Direction	Input or output (configurable)
	DMX Port isolation	Optic and galvanic isolation per port
Ethernet Features	Supported protocols	Art-Net™ , sACN
	Port speed	10/100Mbps
Status Report	Ethernet port connections	Link and Activity LED
	Power	LED indicator
	DMX	LED indicator
Power Input	Power input	12/24V DC
	Power consumption	Max. 4W / 0.17A
Environmental	Storage TEMP	-40°C - +80°C
	Working TEMP.	-20°C - +50°C
	Relative humidity	8%-80%
Other	Ingress Protection rating	IP20
	Net. weight	0.2kg
	Size	148.5*100*25.5mm (W*D*H)
Safety & Warnings	• DO NOT install with power applied to device. • DO NOT expose the device to moisture.	

Mechanical Specifications





